An Effective Theory of Bias Amplification

Arjun Subramonian (they/them)


Meta FAIR

USC ISI NL Seminar

Overview

- Motivation
- An Effective Theory of Bias Amplification [ICLR 2025]
- Conclusion and Future Directions

Motivation




Machine Learning





powerful user-facing products



https://www.testingcatalog.com/claude-ai-teases-claudiainterface-with-a-sidebar-akin-to-chatgpt/



Smile generated by Neural Filters




Neural Filters generates new pixels to adjust the smile.

predictions about individuals at scale




https://surfshark.com/blog/what-is-targeted-advertising




https://www.techfunnel.com/hr-tech/will-automated-hiringsystems-transform-recruitment/

Deep Learning, Deep Problems

- Unfairness issues cause realworld harm
- Why are ML models unfair?
 - Marginalized social groups underrepresented or misrepresented in data





Model design choices

3. Skepticism about the ethical conduct of Al companies is growing, while trust in the fairness of Al is declining. Globally, confidence that Al companies protect personal data fell from 50% in 2023 to 47% in 2024. Likewise, fewer people today believe that Al systems are unbiased and free from discrimination compared to last year.

As ML models are increasingly deployed to make predictions about humans and their relationships at scale...

...it is critical that models are *fair* and do not amplify social inequalities.


Ovalle, A., **Subramonian, A.**, Gautam, V., Gee, G., Chang, K.W. Factoring the Matrix of Domination: A Critical Review and Reimagination of Intersectionality in Al Fairness. AIES 2023.

Overview

- Motivation
- An Effective Theory of Bias Amplification [ICLR 2025]
 - Co-authors: Samuel J. Bell, Levent Sagun, Elvis Dohmatob
- Conclusion and Future Directions










Proliferation of ML

Precise unifying theory of unfairness remains elusive




Greater interpretability



Design better unfairness evaluation and mitigation methods by identifying common sources of unfairness

Interpolate between sparse empirical findings

Precise analytical theory of how model design choices and data distributional properties interact to amplify bias.



Theoretical Setup

- Data: regression problem on dataset from multivariate Gaussian mixture with two groups s=1 and s=2
 - Groups could represent different demographic groups or protected categories

```
(Group ID) Law(s) = Bernoulli(p), (Features) Law(x \mid s) = \mathcal{N}(0, \Sigma_s), more general covariance structure (Ground-truth weights) Law(w_1^*) = \mathcal{N}(0, \Theta/d), Law(w_2^* - w_1^*) = \mathcal{N}(0, \Delta/d), (Labels) Law(y \mid s, x) = \mathcal{N}(f_s^*(x), \sigma_s^2), with f_s^*(x) := x^\top w_s^*.
```

A Tale of Two Learning Paradigms

$$R_s(f) = \mathbb{E}\left[(f(x) - f_s^*(x))^2 \mid s \right]$$

$$EDD = |\mathbb{E} R_2(\hat{f}_2) - \mathbb{E} R_1(\hat{f}_1)| \quad ODD = |\mathbb{E} R_2(\hat{f}) - \mathbb{E} R_1(\hat{f})|$$

$$= \frac{ODD}{EDD} \square 1 \stackrel{\text{loop}}{\underset{\text{def}}{\text{loop}}} \square 1 \stackrel{\text{loop}}{\underset{\text{def}}{\text{loop}} \square 1 \stackrel{\text{loop}}{\underset{\text{def}}{\text{loop}}} \square 1 \stackrel{\text{loop}}{\underset{\text{def}}{\text{loop}} \square 1 \stackrel{\text{loop}}{\underset{\text{def}}{\text{loop}}} \square 1 \stackrel{\text{loop}}{\underset{\text{def}}{\text{loop}} \square 1 \stackrel{\text{loop}}{\underset{\text{def}}}} \square 1 \stackrel{\text{loop}}{\underset{\text{def}}{\text{loop}}} \square 1 \stackrel{\text{loop}}{\underset{\text{def}}} \square 1 \stackrel{\text{loop}}{\underset{\text{def}}{\text{loop}}} \square 1 \stackrel{\text{loop}}{\underset{\text{def}}{\text{loop}}} \square 1 \stackrel{\text{loop}}{\underset{\text{def}}} \square 1 \stackrel{\text{loop}}}{\underset{\text{def}}} \square 1 \stackrel{\text{loop}}{\underset{\text{def}}} \square 1 \stackrel{\text{loop}}{\underset{\text{def}}} \square 1$$

(b) Train each group separately

Bell, S.J., Sagun, L. Simplicity Bias Leads to Amplified Performance Disparities. FAccT 2023.

(c) Train both groups together

Theoretical Setup

 Model: linear two-layer neural network in random features regime:

first-layer weights random and fixed

$$\widehat{w} = S\widehat{\eta} \in \mathbb{R}^d,$$


- $S \in \mathbb{R}^{d \times m}$ is random projection with entries that are IID sampled from $\mathcal{N}(0,1/d)$
- Captures effect of model size on bias amplification
- ℓ_2 -regularization penalty λ

Theoretical Setup

 High-dimensional limit: proportionate scaling captures effect of different feature and parametrization regimes:

$$n, n_1, n_2, d, m \to \infty, \quad d/n \to \phi, m/n \to \psi, m/d \to \gamma$$

- ψ captures rate of parameters to samples
 - $\psi > 1$: overparameterized regime
- ϕ captures rate of features to samples



Bell, S.J. and Sagun, L. Simplicity Bias Leads to Amplified Performance Disparities. FAccT 2023.

Theory of Bias Amplification

group proportions
$$R_s(\hat{f}) \simeq B_s(\hat{f}) + V_s(\hat{f})$$
 parameter and feature rates
$$V_s(\hat{f}) = V(s, p_1, p_2, \sigma_1^2, \sigma_2^2, \phi, \psi, v_{fo}, v_{so}),$$


$$B_s(\hat{f}) = B(s, p_1, p_2, \sigma_1^2, \sigma_2^2, \phi, \psi, v_{fo}, v_{so})$$
 label noises

- $v_{fo}=(e_1,e_2,\tau)$, $v_{so}=(u_1,u_2,\rho)$ satisfy fixed-point equations:
 - Involving λ and 1st and 2nd-order degrees of freedom of covariance matrices $\Sigma_1, \Sigma_2, \Theta, \Delta$
 - Given by operator-valued free probability theory
- Compute $R_{\scriptscriptstyle S}(\hat{f}_{\scriptscriptstyle S})$ by taking limit $p_{\scriptscriptstyle S} \to 1$

Theory of Bias Amplification


Phase diagrams reveal interpolation thresholds at

$$\phi = 1, \psi = 1, \phi = \psi$$



Empirical Validation


- Balanced data $(p_1 = p_2 = 1/2)$
- No spurious correlations ($\Sigma_1=0.5I_d, \Sigma_2=I_d$)



Models can amplify bias even with balanced groups and without spurious correlations.

Empirical Validation

• Use calibration $\lambda \sim 1/t$



May be an optimal regularization penalty or training time to deamplify bias.

Ali, A., Kolter, J.Z., Tibshirani, R.J. A Continuous-Time View of Early Stopping for Least Squares. AISTATS 2019.

Technical Difficulty

- Non-trivial generalization and not special case of existing results in high-dimensional ML literature
 - Requires machinery of free probability theory (FPT)
 - Released tool called auto-fpt to automate FPT calculations

$$V_{s}(\hat{f}) = V_{s}^{(1)}(\hat{f}) + V_{s}^{(2)}(\hat{f}),$$
with $V_{s}^{(j)}(\hat{f}) = \sigma_{j}^{2} \phi \mathbb{E} \operatorname{tr} X_{j}^{\top} X_{j} S(S^{\top} X^{\top} X S + \lambda I_{m})^{-1} S^{\top} \Sigma_{s} S(S^{\top} X^{\top} X S + \lambda I_{m}) S^{\top} / d,$

$$B_{s}(\hat{f}) = \mathbb{E} \|S(S^{\top} X^{\top} X S + \lambda I_{m}) S^{\top} (X_{1}^{\top} X_{1} w_{1}^{*} + X_{2}^{\top} X_{2} w_{2}^{*}) - w_{s}^{*}\|_{\Sigma_{s}}^{2}.$$

Subramonian, A., Dohmatob, E. auto-fpt: Automating Free Probability Theory Calculations for Machine Learning Theory.

Actionable Insights

- Form intuition about when models may amplify bias
 - Disparities in variance of features and labels
 - Overparamaterization and feature-to-sample rate ≈ 1
- Inform hyperparameter selection


Extending our Theory

- More than two groups
- Features and label noise sampled from other distributions
- Different proportionate scaling limits, e.g., d^2/n has finite limit instead of d/n
- Missing features and unknown group information
- Wide fully-trained networks in NTK and lazy regimes

Overview

- Motivation
- An Effective Theory of Bias Amplification [ICLR 2025]
- Conclusion and Future Directions

ML Development Lifecycle



Social Dimensions of Fairness

- Work focuses on technical dimensions of fairness
- Fair ML requires participation of marginalized communities throughout model lifecycle
- Fair ML should combat social inequality and advance justice

QueerInAI, O., Ovalle, A., **Subramonian, A.**, ... Queer In AI: A Case Study in Community-Led Participatory AI. FAccT 2023. QueerInAI, O., Dennler, N., Ovalle, A., Singh, A., Soldaini, L., **Subramonian, A.**, ... Bound by the Bounty: Collaboratively Shaping Evaluation Processes for Queer AI Harms. AIES 2023.

Ovalle, A., **Subramonian, A.**, Gautam, V., Gee, G., Chang, K.W. Factoring the Matrix of Domination: A Critical Review and Reimagination of Intersectionality in AI Fairness. AIES 2023.

Thank you! Questions?

- Motivation
- An Effective Theory of Bias Amplification [ICLR 2025]
- Conclusion and Future Directions

